

# PORTABLE ALUMINIUM FLAGPOLE **BANER**

Mobile flagpole made of anodized aluminum with performance parameters PN-EN 755-2, 6063T66 anti-corrosion protection Al/An 15 µm class 3. Sections made of narrowed tubes.

Flag exposure:  
Rotating socket  
moves in the direction  
of the wind, flag is  
always outstretched

Flag installation:  
Banner arm, bands  
flag weight

Raising and  
lowering the flag:  
by dismantling the  
flagpole or  
using a lift

**PROFILE:**  
Sectional, portable  
aluminium flagpole

**ANODIZING:**  
15 micron

**WALL THICKNESS:**  
2 mm



## TOPS



Rotating socket  
with banner arm  
and a top



Silver onion  
(aluminium)  
(option)



Golden onion  
(brass)  
(option)

## HALYARD SYSTEM



Flag weight



Flag band

Height [m]	3	4	5	6
Sections no. [pcs.]	3	4	5	6
Tube diameter [mm]	50	50	50	50
Recommended maximum flag dimensions [m]	1,2 x 2 [2,4 m <sup>2</sup> ]	1,2 x 2 [2,4 m <sup>2</sup> ]	1,2 x 2 [2,4 m <sup>2</sup> ]	1,2 x 2 [2,4 m <sup>2</sup> ]