

ALUMINIUM SECTIONAL FLAGPOLE **BANER**

Sectional flagpole made of anodized aluminum with performance parameters PN-EN 755-2, 6063T66 anti-corrosion protection Al/An 15 µm class 3. Sections connected with reducing sleeves.

Flag exposure:
Rotating socket moves in the direction of the wind, flag is always outstretched

Flag installation:
Banner arm, bands flag weight

Raising and lowering the flag:
by dismantling the flagpole or using a lift



Reduction sleeve

ANODIZING:
15 micron

Wall thickness:
[5-6 m]
2/2,5 mm
[7-10m]
2/2,5/2,5 mm
[11-12 m]
2/2,5/2,5/3,5 mm



TOPS



Rotating socket with banner arm and a top



Silver onion (aluminium) (option)



Golden onion (brass) (option)

FLAG ASSEMBLY




Flag weight



Flag band


BASES



Ground sleeve (flagpoles 5-10 m)
To be installed in a foundation



Hinged base (flagpoles 5-12 m)
To be installed in a foundation



Portable base (for pavement tiles 50x50 cm)

Height [m]	5	6	7	8	9	10	11	12
Sections no. [pcs.]	2	2	3	3	3	3	4	4
Tube diameter [mm]	50/65	50/65	50/65/80	50/65/80	50/65/80	50/65/80	50/65/80/95	50/65/80/95
Recommended maximum flag dimensions [m]	1,2 x 3 [3,6 m²]	1,2 x 3 [3,6 m²]	1,2 x 3,5 [4,2 m²]	1,2 x 3,5 [4,2 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]